

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition	Errors
1	IS&R	L1	909	(257/432).CCLS.	US-PGPUB; USPAT	2005/1 0/26 11:41			
2	BRS	L2	50	(photodetector or photodiode or pd) with (integral or integrally or directly) with filter.ti,ab,clm.	US-PGPUB; USPAT	2005/1 0/26 11:43			
3	BRS	L3	1508	(photodetector or photodiode or pd) with filter.ti,ab,clm.	US-PGPUB; USPAT	2005/1 0/26 16:56			
4	BRS	L4	2395	1 or 2 or 3	US-PGPUB; USPAT	2005/1 0/26 11:43			
5	BRS	L5	343427	(1 near2 (shape or shaped)) or (right adj angle) or ("90" adj (degree or degrees))	US-PGPUB; USPAT	2005/1 0/26 11:46			
6	BRS	L6	198	4 and 5	US-PGPUB; USPAT	2005/1 0/26 11:47			
7	BRS	L15	71	(photodetector or photodiode or pd) with (1 near2 (shape or shaped))	US-PGPUB; USPAT	2005/1 0/26 16:57			
8	BRS	L16	70	15 not 6	US-PGPUB; USPAT	2005/1 0/26 16:57			